

HARDROCK

HARDROCK SPORT WOMEN'S



Blue



Features/Updates

- Specialized "Designs For Women" geometry A1 Premium aluminum frame featuring forged drop outs with eyelets, reinforced disc mount and forged alloy hanger, manipulated TT, and DT with 3D box gusset
- Specialized Mobius alloy stem
- RST Gilla T4 fork with 100mm travel, preload adjust, Cr-Mo steerer and coil/MCU spring
- Tektro linear-pull brakes with stainless steel lead pipe
- Alex double-wall rims w/ CNC braking surface

PART NO.	MODEL	SIZE	COLOR
9140-3001	HARDROCK SPORT WOMEN'S RIM	S	BLUE
9140-3002	HARDROCK SPORT WOMEN'S RIM	M	BLUE
9140-3003	HARDROCK SPORT WOMEN'S RIM	L	BLUE

HARDROCK SPORT WOMEN'S RIM

FRAME	A1 Premium Aluminum, Designs For Women geometry, DT/HT 3D box gusset, forged dropouts w/ reinforced disc mount and eyelets, replaceable forged alloy derailleur hanger, designed for 100mm travel fork
FORK	RST Gilla T4, 100mm travel, preload adjust, Cr-Mo steerer, coil/MCU spring
HEADSET	1 1/8" threadless, sealed loose ball, alloy cap
STEM	Specialized Mobius, alloy, 10 degree rise
HANDLEBARS	Alloy, 38mm rise, 9 degree sweep
TAPE / GRIPS	Specialized "Telluride" double density Kraton
FRONT BRAKE	Tektro "V", linear spring, stainless steel pipe
REAR BRAKE	Tektro "V", linear spring, stainless steel pipe
BRAKE LEVERS	Shimano Altus
FRONT DERAILLEUR	Shimano Acera, 31.8mm clamp, bottom pull
REAR DERAILLEUR	Shimano Acera
SHIFT LEVERS	Shimano Altus
CASSETTE	Shimano HG-50, 8-speed, 11x32t
CHAIN	Shimano IG-31
CRANKSET	Truvativ ISOFlow, alloy, capless bolts
CHAINRINGS	42t Cr-Mo x 32t heat-treated Cr-Mo x 22t heat-treated Cr-Mo, replaceable
BOTTOM BRACKET	Truvativ, 68x113mm, square taper, sealed cartridge bearing w/ drive side crank stop
PEDALS	Dual sided, composite body, steel cage, toe clip compatible
RIMS	Alex DM-20, 26"x1.5", double wall, machined side wall, black
FRONT HUB	Joy-Tech, 32 hole, ground race double sealed loose ball w/ alloy QR
REAR HUB	Joy-Tech, freehub, 32 hole, ground race double sealed loose ball w/ alloy QR
SPOKES	2.0mm (14g) stainless steel, brass nipples, L267/R267mm front, L265/R264mm rear
FRONT TIRE	Specialized Enduro Sport, 26"x2.0", wire bead
REAR TIRE	Specialized Enduro Sport, 26"x2.0", wire bead
TUBES	Specialized schraeder valve
SADDLE	Specialized Body Geometry Sport ATB Women's
SEAT POST	Alloy 30.9mmx300/350mm, micro adjust
SEAT BINDER	Alloy QR, 36mm I.D.
NOTES	Chain stay protector, reflectors, clear coat, owners manual

All specs are subject to change without notice.