

HARDROCK

HARDROCK XC



Charcoal

Features/Updates

- A1 Premium Aluminum frame with 3D Box gusset on downtube and forged dropouts with eyelets
- RST Capa T4 fork with 80mm travel and preload adjust
- Wheelset features Alex alloy rims with ground sidewalls for improved braking, stainless steel spokes
- Truvativ X-Flow crank and sealed cartridge BB
- Body Geometry Sport ATB saddle

| PART NO. | MODEL | SIZE | COLOR |
|-----------|-----------------|------|----------|
| 9140-4113 | HARDROCK XC RIM | XS | CHARCOAL |
| 9140-4115 | HARDROCK XC RIM | S | CHARCOAL |
| 9140-4117 | HARDROCK XC RIM | M | CHARCOAL |
| 9140-4119 | HARDROCK XC RIM | L | CHARCOAL |
| 9140-4121 | HARDROCK XC RIM | XL | CHARCOAL |

HARDROCK XC RIM

| | |
|------------------|--|
| FRAME | A1 Premium Aluminum, 3D box gusset HT/DT, TT gusset, forged dropouts w/ eyelets and replaceable hanger with eyelets for 80mm travel fork |
| FORK | RST Capa T4, 80mm travel, Cr-Mo steerer, preload adjust |
| HEADSET | 1 1/8" threadless, sealed loose ball, alloy cap |
| STEM | Alloy, 15 degree rise |
| HANDLEBARS | Steel, 40mm rise, 9 degree sweep |
| TAPE / GRIPS | Kraton "Revo" twist design |
| FRONT BRAKE | Tekro "V", linear spring, stainless steel pipe |
| REAR BRAKE | Tekro "V", linear spring, stainless steel pipe |
| BRAKE LEVERS | Tekro "V" alloy, "Revo" compatible |
| FRONT DERAILLEUR | Shimano C-050, 31.8mm clamp, bottom pull |
| REAR DERAILLEUR | Shimano Altus |
| SHIFT LEVERS | Shimano Revo RS-41, twist shift |
| FREEWHEEL | Shimano MF-HG37, 7-speed, 14x28t freewheel |
| CHAIN | Shimano IG-31 |
| CRANKSET | Truvativ X-Flow, alloy w/ capless bolts |
| CHAINRINGS | 42t Cr-Mo x 34t heat-treated Cr-Mo x24t heat-treated Cr-Mo, replaceable |
| BOTTOM BRACKET | Truvativ, 68x113mm, square taper, sealed cartridge bearing with drive side crank stop |
| PEDALS | Dual sided, composite, clip compatible, with reflector |
| RIMS | Alex, 26"x1.5", single wall w/ ground side wall |
| FRONT HUB | Joy-Tech, 32 hole, double sealed loose ball w/ alloy QR |
| REAR HUB | Joy-Tech, freewheel, 32 hole, double sealed loose ball with alloy QR |
| SPOKES | 2.0mm (14g) stainless steel, brass nipples, L266/R266mm front, L265/R264mm rear |
| FRONT TIRE | Specialized Enduro Sport, 26"x2.0", wire bead |
| REAR TIRE | Specialized Enduro Sport, 26"x2.0", wire bead |
| TUBES | Specialized schraeder valve |
| SADDLE | Specialized Body Geometry Sport ATB |
| SEAT POST | Alloy 30.9mmx300/350mm, micro adjust |
| SEAT BINDER | Alloy QR, 36mm I.D. |
| NOTES | Chain stay protector, reflectors, clear coat, owners manual |

All specs are subject to change without notice.