

STUMPJUMPER FSR

FRAME GEOMETRIES

Stumpjumper

FSR

This bike applies technology to make it light, efficient, nimble, and fun in cross-country trail situations.

100mm of FSR Suspension is the proven superior suspension system, delivering:

- Superior Comfort
- Maximum Control
- Highest Efficiency

Triad Shock from Fox (On top 3 models)

- Efficiency boost from Fox's Pro Pedal platform
- Ability to "turn off" Pro Pedal, for optimal small bump sensitivity
- "Lockout" setting for fully rigid rear end

TransForm Monocoque

- Stronger – material is strategically placed in line with force vectors applied to the frame, and weld areas are moved away from highly stressed sections
- Lighter – a single monocoque replaces multiple components
- More precise handling – a stiff front end means razor-sharp handling

STUMPJUMPER FSR

Size	Small	Medium	Large	X-Large	Wmn S	Wmn M
Stand Over Height	732mm	737mm	741mm	748mm	729mm	732mm
Top Tube Length	551mm	587mm	612mm	638mm	535mm	560mm
Head Tube Length	100mm	110mm	120mm	150mm	100mm	110mm
Head Angle	70.5°	70.5°	70.5°	70.5°	70.5°	70.5°
Seat Angle	73°	73°	73°	73°	73°	73°
Wheel Base	1038mm	1075mm	1100mm	1128mm	1022mm	1047mm
Chain Stay Length	424mm	424mm	424mm	424mm	424mm	424mm
Fork Offset	39mm	39mm	39mm	39mm	39mm	39mm
Stem Length	90mm	100mm	110mm	120mm	75mm	75mm
H/B Width	640mm	640mm	640mm	640mm	640mm	640mm
Crank Length	170mm	175mm	175mm	175mm	170mm	170mm
BB Height	325mm	325mm	325mm	325mm	325mm	325mm
Seat Post Length	350mm	350mm	400mm	400mm	350mm	350mm

* TT is measured horizontally from center of HT to center of ST